

UNOCAL PORSF 00049
11.3.125.1v
07/12/85Product Name: UNOCAL KOOLKUT II HD
PRODUCT CODE NO: 04780

ISSUE DATE: 7/12/85

PAGE 1 OF 4

MANUFACTURER:UNOCAL REFINING & MARKETING DIVISION
UNION OIL COMPANY OF CALIFORNIA
1201 W. 5TH STREET
LOS ANGELES, CALIFORNIA 90017CONTACT FOR FURTHER INFORMATION:
MSDS COORDINATOR (213) 977-7589**Transportation Emergencies:**Call CHEMTREC
(800) 424-9300 Cont. U.S.
(202) 483-7616 (Collect)
from Alaska & Hawaii**Health Emergencies:**CALL LOS ANGELES POISON
INFORMATION CENTER (24 hrs.)
(213) 664-2121**PRODUCT IDENTIFICATION****PRODUCT NAME:** UNOCAL KOOLKUT II HD**SYNONYMS:** UNION KOOLKUT II HD**GENERIC NAME:** INDUSTRIAL OILS**CHEMICAL FAMILY:** PETROLEUM HYDROCARBON**DOT PROPER
SHIPPING NAME:** NOT APPLICABLE**ID NUMBER:** NONE**SECTION I - INGREDIENTS**

TLV UNITS AGENCY TYPE

OIL MIST, IF GENERATED

5.00 MG/M3 OSHA FULL TERM TWA

THE IDENTITIES OF INGREDIENTS THAT ARE TRADE SECRETS ARE EXCLUDED FROM
THIS LIST.**SECTION II - EMERGENCY AND FIRST AID PROCEDURES**

EMERGENCY

Have physician call LOS ANGELES POISON
INFORMATION CENTER (24 hrs.) (213) 664-2121**EYE CONTACT:**FOR DIRECT CONTACT, FLUSH THE AFFECTED EYE(S) WITH CLEAN WATER. IF IRRITATION OR
REDNESS DEVELOPS, SEEK MEDICAL ATTENTION.**SKIN CONTACT:**DO NOT USE GASOLINES, THINNERS OR SOLVENTS TO REMOVE PRODUCT FROM SKIN. WIPE MATERIAL
FROM SKIN AND REMOVE CONTAMINATED CLOTHING. CLEANSE AFFECTED AREA(S) THOROUGHLY BY
WASHING WITH SOAP AND WATER AND, IF NECESSARY, A WATERLESS SKIN CLEANSER. IF
IRRITATION OR REDNESS DEVELOPS AND PERSISTS, SEEK MEDICAL ATTENTION.**INHALATION (BREATHING):**IF IRRITATION OF NOSE OR THROAT DEVELOPS, MOVE AWAY FROM SOURCE OF EXPOSURE AND INTO
FRESH AIR. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. IF VICTIM IS NOT BREATHING
OR IF BREATHING DIFFICULTIES DEVELOP, ARTIFICIAL RESPIRATION OR OXYGEN SHOULD BE
ADMINISTERED BY QUALIFIED PERSONNEL. SEEK IMMEDIATE MEDICAL ATTENTION.**INGESTION (SWALLOWING):**IF VICTIM IS CONSCIOUS AND ALERT, GIVE 2 TO 3 CUPS OF MILK OR WATER TO DRINK. SEEK
MEDICAL ATTENTION. TO PHYSICIAN: EMESIS OR LAYAGE IS NOT RECOMMENDED FOR INGESTIONS
OF MINUTE QUANTITIES OR TASTES OF MOST HYDROCARBONS. MEDICAL OPINION IS DIVIDED FOR
LARGER INGESTIONS. EMESIS OR LAYAGE HAS BEEN RECOMMENDED FOR THOSE PETROLEUM
PRODUCTS WHICH HAVE A HIGH ORAL TOXICITY. GASTRIC LAYAGE WITH A CUFFED ENDOTRACHEAL
TUBE IS RECOMMENDED BY SOME PHYSICIANS TO PREVENT ASPIRATION.

USEPA SF



1265449

Product Name: UNOCAL KOOLKUT II HD
PRODUCT CODE NO: 04780

ISSUE DATE: 7/12/85

00049
PAGE 2 OF 4

SECTION III - POTENTIAL ADVERSE HEALTH EFFECTS

EYE CONTACT:

THIS MATERIAL MAY CAUSE EYE IRRITATION. DIRECT CONTACT MAY CAUSE BURNING, TEARING AND REDNESS.

SKIN CONTACT:

THIS MATERIAL MAY CAUSE SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE REDNESS, BURNING AND DERMATITIS.

INHALATION (BREATHING):

EXPOSURE TO MISTS, OR PROLONGED OR REPEATED EXPOSURE TO FUMES OR VAPORS THAT MAY BE GENERATED WHEN THIS MATERIAL IS HEATED, MAY CAUSE IRRITATION OF NOSE AND THROAT.

INGESTION (SWALLOWING):

ACCIDENTAL INGESTION OF THIS MATERIAL MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT.

SECTION IV - SPECIAL PROTECTION INFORMATION

VENTILATION:

IF CURRENT VENTILATION PRACTICES ARE NOT ADEQUATE IN MAINTAINING AIRBORNE CONCENTRATIONS BELOW THE ESTABLISHED EXPOSURE LIMITS (SEE SECTION I), ADDITIONAL VENTILATION OR EXHAUST SYSTEMS MAY BE REQUIRED.

RESPIRATORY PROTECTION:

IF AIRBORNE CONCENTRATIONS EXCEED RECOMMENDED EXPOSURE LIMITS, A SUITABLE FILTER-TYPE RESPIRATOR SHOULD BE WORN. (SEE SECTION I.)

PROTECTIVE GLOVES:

THE USE OF GLOVES IMPERMEABLE TO THE SPECIFIC MATERIAL HANDLED IS ADVISED TO PREVENT SKIN CONTACT AND POSSIBLE IRRITATION.

EYE PROTECTION:

APPROVED EYE PROTECTION TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY IS RECOMMENDED.

OTHER PROTECTIVE EQUIPMENT:

IT IS SUGGESTED THAT A SOURCE OF CLEAN WATER BE AVAILABLE IN WORK AREA FOR FLUSHING EYES AND SKIN. BARRIER CREAMS THAT ARE SPECIFIC FOR OIL-BASED MATERIALS ARE RECOMMENDED WHEN GLOVES ARE IMPRACTICAL.

SECTION V - REACTIVITY DATA

STABILITY:

STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID CONTACT WITH ANY SOURCE OF IGNITION.

INCOMPATIBILITY (MATERIALS TO AVOID):

AVOID CONTACT WITH STRONG ACIDS, BASES, AND OXIDIZING AGENTS. EXTENDED EXPOSURE TO HIGH TEMPERATURES MAY CAUSE DECOMPOSITION.

Product Name: UNOCAL KOOLKUT II HD
PRODUCT CODE NO: 04780

ISSUE DATE: 7/12/85

00049
PAGE 3 OF 4

SECTION V - REACTIVITY DATA

HAZARDOUS DECOMPOSITION PRODUCTS:

THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD MAJOR AMOUNTS OF OXIDES OF CARBON AND MINOR AMOUNTS OF OXIDES OF SULFUR AND NITROGEN. ALSO, MINOR AMOUNTS OF OXIDES OF CHLORINE BE FORMED.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR

SECTION VI - SPILL OR LEAK PROCEDURES

HIGHWAY OR RAILWAY SPILLS
Call CHEMTREC (800) 424-9300 Cont. U.S.
(Collect) (202) 483-7616 from Alaska & Hawaii

PRECAUTIONS IN CASE OF RELEASE OR SPILL:

COLLECT LEAKING LIQUID IN SEALABLE CONTAINERS. ABSORB SPILLED LIQUID IN SAND OR INERT ABSORBANT. CONTACT FIRE AUTHORITIES AND APPROPRIATE STATE/LOCAL AGENCIES. IF SPILL OF ANY AMOUNT IS MADE INTO OR UPON U.S. NAVIGABLE WATERS, THE CONTIGUOUS ZONE, OR ADJOINING SHORELINES, NOTIFY COAST GUARD NATIONAL RESPONSE CENTER (PHONE NUMBER 800-424-8802).

WASTE DISPOSAL METHOD:

DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE, AND FEDERAL REGULATIONS.

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS:

STORE IN A COOL, DRY LOCATION. KEEP AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION V). AVOID GENERATING OIL MISTS WHILE HANDLING. AVOID PROLONGED OR REPEATED SKIN CONTACT. WASH THOROUGHLY AFTER HANDLING. DO NOT WEAR OIL-SOAKED CLOTHING OR SHOES.

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

HAZARD RANKING

NFPA	HEALTH HAZARD: 0	0 = LEAST	DOT FLAMMABILITY	FLASH POINT
HAZARD	FLAMMABILITY: 1	1 = SLIGHT	CLASSIFICATION	
CLASS	REACTIVITY: 0	2 = MODERATE		
	OTHER:	3 = HIGH	NOT REGULATED	414, COC F
		4 = EXTREME		212 C

EXTINGUISHING MEDIA:

EXTINGUISH WITH DRY CHEMICAL, CO2, WATER SPRAY, FOAM, SAND OR EARTH. WATER AND FOAM MAY CAUSE FROTHING.

FIRE & EXPLOSION HAZARDS:

THIS MATERIAL WILL BURN, BUT WILL NOT IGNITE READILY.

FIRE FIGHTING PROCEDURES:

WATER SPRAY MAY BE USEFUL IN MINIMIZING VAPORS AND COOLING CONTAINERS EXPOSED TO HEAT AND FLAME. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. MOVE UNDAMAGED CONTAINERS FROM FIRE AREA IF YOU CAN DO SO WITHOUT RISK.

Product Name: UNOCAL KOOLKUT II HD
PRODUCT CODE NO: 04780

ISSUE DATE: 7/12/85

00049
PAGE 4 OF 4

SECTION IX - PHYSICAL DATA

<u>APPROX. BOILING RANGE</u>	<u>VAPOR DENSITY</u>	<u>EVAPORATION RATE</u>	<u>% VOLATILE</u>
ABOVE 600 F (316) C	HEAVIER THAN AIR	SLOWER THAN ETHER	NEGLIGIBLE
<u>% SOLUBILITY IN WATER</u>	<u>SPECIFIC GRAVITY</u>	<u>APPEARANCE</u>	<u>ODOR</u>
NEGLIGIBLE	0.90	CLEAR, BROWN	CHARACTERISTIC

SECTION XI - DOCUMENTARY INFORMATION

ISSUE DATE: 7/12/85 PREV. DATE: 0/ 0/ 0 PRODUCT CODE NO. 04780

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.